

Solutions for Power Switching and Monitoring

June
30th 2021



When energy matters

UPS & Critical power solutions



7 solutions

- Modular UPS
- Single-phase UPS
- Three-phase UPS
- Static Transfer System (STS)
- Industrial and transformer based UPS
- UPS for special applications
- Connected services

50 years
of expertise

3 levels of protection

according to your criticality

Prime | Superior | Ultimate

3 offers

Standard | Adapted | Custom

Product Name	Rating	Item code	Product Description	List Price in INR
ITYS-E	1 kVA	ITY-E-TW010B-I	1 kVA Single phase online UPS with Built-in Battery	26,928
	2 kVA	ITY-E-TW020B-I	2 kVA Single phase online UPS with Built-in Battery	46,410
	3 kVA	ITY-E-TW030B-I	3 kVA Single phase online UPS with Built-in Battery	53,040
	1 kVA	ITY-E-TW010LB-I	1 kVA Single phase online UPS with External Battery option	24,174
	2 kVA	ITY-E-TW020LB-I	2 kVA Single phase online UPS with External Battery option	40,800
	3 kVA	ITY-E-TW030LB-I	3 kVA Single phase online UPS with External Battery option	44,574
	6 kVA	ITY-E-TW060LB	6 kVA Single phase online UPS with External Battery option	83,640
	10 kVA	ITY-E-TW100LB	10 kVA Single phase online UPS with External Battery option	1,08,120
ITYS	10 kVA	ITY2-TW110XLB	10 kVA Single phase online UPS 3/1 COMBO with External Battery option	1,66,400
	20 kVA	ITY2-TW210XLB	20 kVA Single phase online UPS 3/1 COMBO with External Battery option	2,83,920
	Parallel kit	ITY2-PAR10-20	Parallel Kit for 10-20kVA COMBO 1+1	13,700
NETYS RT	5 kVA	NRT3-U5000C	5 kVA Single Phase rack mountable online UPS, with External Battery Option	1,03,950
	7 kVA	NRT3-U7000CLAC	7 kVA Single Phase rack mountable online UPS, with External Battery Option	1,41,020
	11 kVA	NRT3-U11000CLAC	11 kVA Single Phase rack mountable online UPS, with External Battery Option	1,53,300
STATYS XS	16A	3310016001	Static Transfer Switch 16A 230 V 1P 2 WIRES 2 POLE SWITCHING(19" Rack mountable)	57,750
	32A	3310032001	Static Transfer Switch 32A 230 V 1P 2 WIRES 2 POLE SWITCHING(19" Rack mountable)	1,05,000

*Note: Online UPS available from 1 kVA to 5400 kVA, Static transfer switches (STS) available up to 1800 A. For higher rating UPS & STS, send your query to info.in@socomec.com



Load Break Switches

COMO

From 32 to 63A

Solution		OPEN EXECUTION							
		Din Rail/Black Plate				Door Mounting			
		Direct Handle Version		External Handle Version*		External operation Version* with screw		Quick Fix Version*	
Rating	Poles	Reference	LP (₹)	Reference	LP (₹)	Reference	LP (₹)	Reference	LP (₹)
32A	3	21113003G	727	21113103G	663	21113203G	663	21113303G	663
63A	3	21113005G	876	21113105G	822	21113205G	893	21113305G	893

* references are only for Switch

Accessories for Din Rail/Back Plate mounting

Rating	4th Pole	LP (₹)	External handle K1 type IP65 with Guided Shaft	LP (₹)	Extension shaft	LP (₹)	Aux Contact NO + NC	LP (₹)	Neutral Pole	LP (₹)
32A	21111003G	249	21131112G (Blue/Black)	191	21132200G (200mm)	128	21134000G	313	21111056G	313
63A	21111005G	291	21131113G (Red /Yellow)		21132320G (320mm)	175				

Accessories for Door mounting

Rating	4th Pole	LP (₹)	External handle K1 type IP65 with Screw	LP (₹)	External handle K1 type IP65 - Quickfix	LP (₹)	Aux Contact NO + NC	LP (₹)	Neutral Pole	LP (₹)
32A	21111203G	254	21131322G (Blue/Black)	194	21131332G (Blue/Black)	194	21134200G	319	21111256G	319
63A	21111205G	297	21131323G (Red /Yellow)		21131333G (Red/Yellow)					

Enclosed Load Break Switches

COMO

From 20 to 125A







Pole	20A		25A		32A		40A	
	Reference	LP (₹)	Reference	LP (₹)	Reference	LP (₹)	Reference	LP (₹)
3Pole (Yellow/Red)	21153401G	1315	21153402G	1419	21153403G	1458	21153404G	1593
3Pole (Blue/Grey)	21153301G	1315	21153302G	1419	21153303G	1458	21153304G	1593
4Pole (Yellow/Red)	21154401G	1475	21154402G	1593	21154403G	1634	21154404G	1817
4Pole (Blue/Grey)	21154301G	1475	21154302G	1593	21154303G	1634	21154304G	1817
Pole	63A		80A		100A		125A	
	Reference	LP (₹)	Reference	LP (₹)	Reference	LP (₹)	Reference	LP (₹)
3Pole (Yellow/Red)	21153406G	2122	21153408G	4196	21153409G	5305	21153412G	9814
3Pole (Blue/Grey)	21153306G	2122	21153308G	4196	21153309G	5305	21153312G	9814
4Pole (Yellow/Red)	21154406G	2652	21154408G	4668	21154409G	6076	21154412G	10450
4Pole (Blue/Grey)	21154306G	2652	21154308G	4668	21154309G	6076	21154312G	10450



Load Break Switches

SIRCO

Conforms to IS/IEC 60947-3 up to AC23A¹, Front operated 3 or 4 pole 415 V, 50 Hz.

SOLUTION			OPEN EXECUTION				ENCLOSED SOLUTION			
			KIT Type 1		KIT Type 2		Enclosed Switch		Extension Box	
Standard Configuration Includes										
			<ul style="list-style-type: none"> • Switch • Interphase barriers from frame B3 and above • Direct Handle 		<ul style="list-style-type: none"> • Switch • Interphase barriers from frame B3 and above • External Handle • Extension Shaft 200mm 		<ul style="list-style-type: none"> • Enclosure • Switch • Interphase barriers from frame B3 and above • External Handle • Extension Shaft 		Suitable for Top or Bottom Assembly (Price is for 1 number of extension box)	
Frame	Rating	Poles	Reference	LP (₹)	Reference	LP (₹)	Reference	LP (₹)	Reference	LP (₹)
B3	125A	3P	26K13012A	4628	26K23012A	5033	26E13012A	7410	26E10002A	1563
	160A		26K13016A	5859	26K23016A	6265	26E13016A	8969		
	200A CD		26K13019A	6085	26K23019A	6490	26E13019A	9242		
B4	200A		26K13020A	6657	26K23020A	7061	26E13020A	9407	26E10003A	2417
	250A		26K13025A	8650	26K23025A	9056	26E13025A	12271		
	315A CD		26K13030A	8718	26K23030A	9125	26E13030A	14141		
B5	400A CD		26K13039A	10841	26K23039A	11247	26E13039A	15377	26E10004A	3080
	315A		26K13031A	9316	26K23031A	9720	26E13031A	15082		
	400A		26K13040A	12945	26K23040A	13352	26E13040A	18135		
	500A		26K13050A	14198	26K23050A	14602	26E13050A	19976		
B6	630A		26K13063A	15605	26K23063A	16011	26E13063A	21725	-	-
	800A CD		26K13079A	18479	26K23079A	19155	-	-		
	1000A	26K13100A	35539	26K23100A	36216	26E13100A	47384			
B7	1250A CD	26K13124A	40564	26K23124A	41240	-	-	26E10006A	9058	
	1250A	26K13125A	48579	26K23125A	49254	26E13125A	65881			
B8	1600A	26K13160A	65589	26K23160A	66264	26E13160A	86834	26E10007A	11480	
	1800A	26K13180A	72339	26K23180A	73014	-	-			
B2*	2000A	26K13200A	81433	26K23200A	82785	-	-	-	-	
	2500A	26K13250A	112311	26K23250A	113663	-	-			
	3200A	26K13320A	150636	26K23320A	151989	-	-			
B3	63A	26K14006A	2628	26K24006A	2999	26E14006A	4143	26E10001A	919	
	100A	26K14010A	4507	26K24010A	4878	26E14010A	5926			
	125A CD	26K14011A	4931	26K24011A	5303	26E14011A	6872			
B4	160A	26K14016A	6893	26K24016A	7370	26E14016A	9729	26E10002A	1563	
	200A CD	26K14019A	7158	26K24019A	7636	26E14019A	9809			
	200A	26K14020A	7831	26K24020A	8308	26E14020A	11251			
B5	250A	26K14025A	10178	26K24025A	10654	26E14025A	13247	26E10003A	2417	
	315A CD	26K14030A	10256	26K24030A	10734	26E14030A	15467			
	400A CD	26K14039A	12754	26K24039A	13558	26E14039A	17768			
B6	315A	26K14031A	10959	26K24031A	13231	26E14031A	15538	26E10004A	3080	
	400A	26K14040A	15229	26K24040A	15707	26E14040A	21084			
	500A	26K14050A	16702	26K24050A	17180	26E14050A	23161			
	630A	26K14063A	18359	26K24063A	18836	26E14063A	25176			
B7	800A CD	26K14079A	21740	26K24079A	22535	-	-	-	-	
	1000A	26K14100A	41811	26K24100A	42607	26E14100A	54932			
B8	1250A CD	26K14124A	47721	26K24124A	48516	-	-	26E10006A	9058	
	1250A	26K14125A	57152	26K24125A	57946	26E14125A	75887			
	1600A	26K14160A	77163	26K24160A	77958	26E14160A	100044			
B2*	1800A	26K14180A	85104	26K24180A	85898	-	-	26E10007A	11480	
	2000A	26K14200A	95803	26K24200A	97394	-	-			
	2500A	26K14250A	132130	26K24250A	133721	-	-			
B3	3200A	26K14320A	177219	26K24320A	178810	-	-	-	-	

CD - Compact design

1) please refer technical literature for exact technical characteristics

* Phase Barrier & Shaft is not available in frame B2

Rating 125A & 800A are also available in AC-23A category

SIRCO Accessories



Frame	Direct Handle	LP (₹)	External Handle	LP (₹)	1st Aux Contact (1 NO/NC)	LP (₹)	2nd Aux Contact (1 NO/NC)	LP (₹)
B2	42990001A	378	-	-	26091020A	172	26092020A	285
B3	26995042A	378	14212111A	1219	26990031A	424	26990032A	499
B4	26995052A	689	14212111A	1219	26990031A	424	26990032A	499
B5	26995052A	689	14212111A	1219	26990031A	424	26990032A	499
B6*	27997012A	2749	14433111A	1892	26990031A	424	26990032A	499
B7*	27997012A	2749	14433111A	1892	26990031A	424	26990032A	499
B8*	27997012A	2749	14538111A	11918	26990031A	424	26990032A	499

* Handle for frames B6 to B8 are double arms handle



Frame	Shaft 200mm	LP (₹)	Shaft 250mm	LP (₹)	Shaft 320mm	LP (₹)
B3	14001020A	424	14001025A	541	14001032A	594
B4	14001020A	424	14001025A	541	14001032A	594
B5	14001020A	424	14001025A	541	14001032A	594
B6	14011520A	871	-	-	14011532A	1092
B7	14011520A	871	-	-	14011532A	1092
B8	27993015A	2823	-	-	27993018A	3182



Frame	Interphase barrier - 3P	LP (₹)	Interphase barrier - 4P	LP (₹)	Spreaders - 3P	LP (₹)	Spreaders - 4P	LP (₹)
B2	-	-	-	-	-	-	41064012A	345
B3	29985033A	174	29985034A	251	41063016A	340	41064016A	460
B4	29985023A	206	29985024A	299	41063025A	507	41064025A	689
B5	29985013A	238	29985014A	347	41063040A (400A)	687	41064040A (400A)	933
B5	-	-	-	-	41063050A (500A)	909	41064050A (500A)	1106
B5	-	-	-	-	41063063A (630A)	1842	41064063A (630A)	2457



Frame	Terminal Shroud - 3P	LP (₹)	Terminal Shroud - 4P	LP (₹)	Terminal Screen Standard - 3P	LP (₹)	Terminal Screen Standard - 4P	LP (₹)
B2	-	-	29944008A	303	-	-	-	-
B3	26943014A	632	26944014A	752	26983012A	510	26984012A	578
B4	26943021A	737	26944021A	859	26983020A	510	26984020A	578
B5	26943051A	1124	26944051A	1288	26983050A	653	26984050A	740
B6	-	-	-	-	26983080A	1310	26984080A	1486
B7	-	-	-	-	26983120A	1944	26984120A	2203
B8	-	-	-	-	26983200A	3490	26984200A	3954



Frame	Terminal Screen Wide - Top - 3P	LP (₹)	Terminal Screen Wide - Bottom - 3P	LP (₹)	Terminal Screen wide Top/Bottom - 4P	LP (₹)
B3	26983013A	612	26988013A	612	26984013A	694
B4	26983021A	612	26988021A	612	26984021A	694
B5	26983051A	783	26988051A	783	26984051A	888
B6	26983081A	1573	26988081A	1573	26984081A	1783

Manual Transfer Switching Equipment

63A to 3200A



NEW SIRCOVER

MORE

RELIABLE | SECURE | ROBUST
ADAPTABLE | FLEXIBLE | DURABLE

socomec
Innovative Power Solutions



Manual Transfer Switching Equipment

SIRCOVER

Conforms to IEC 60947-6-1 up to AC33B¹, IS/IEC 60947-3 up to AC-23A¹,
Front operated 3 or 4 pole 415 V, 50 Hz.

SOLUTION			OPEN EXECUTION				ENCLOSED SOLUTION				
			KIT Type 1		KIT Type 2		Enclosed Switch		Extention Box		
Standard Configuration Includes											
			<ul style="list-style-type: none"> • Transfer switch • Direct handle • Bridging Bars up to 1600 A • Interphase barriers from frame B3 and above 		<ul style="list-style-type: none"> • Transfer switch • Bridging Bars up to 1600 A • Extended handle • 200 mm shaft • Interphase barriers from frame B3 and above 		<ul style="list-style-type: none"> • Transfer switch • Extended handle • Bridging Bars up to 1600 A • Extension shaft • Interphase barriers from frame B3 and above 		Suitable for Top or Bottom Assembly (Price is for 1 number of extension box)		
Frame	Rating	Poles	Reference	LP (₹)	Reference	LP (₹)	Reference	LP (₹)	Reference	LP (₹)	
B3	125A	3P	41K13013A	9073	41K23013A	9316	41E13013A	12992	41E10002A	2719	
	160A		41K13016A	9773	41K23016A	10190	41E13016A	14250			
	200A		41K13020A	11877	41K23020A	12291	41E13020A	16363			
	250A		41K13025A	17311	41K23025A	17726	41E13025A	22640	41E10003A	2906	
	B4		315A	41K13031A	18297	41K23031A	18711	41E13031A	23660	41E10004A	4283
			400A	41K13040A	26915	41K23040A	27331	41E13040A	34601		
	B5		500A	41K13050A	28879	41K23050A	30380	41E13050A	37384	41E10005A	4587
			630A	41K13063A	31739	41K23063A	32155	41E13063A	40005		
B6	CD800A	41K13079A	42931	41K23079A	43346	-	-	-	-		
	1000A	41K13100A	81422	41K23100A	82115	41E13100A	105616	41E10006A	10198		
B7	1250A	41K13120A	108761	41K23120A	109454	41E13120A	146753	41E10007A	32104		
	1600A	41K13160A	127433	41K23160A	128125	41E13160A	198998				
B8	2000A	41K13200A	199439	41K23200A	200823	41E13200A	256688	41E10008A	41322		
	2500A	41K13250A	266113	41K23250A	267497	41E13250A	341437				
B2*	3200A	41K13320A	364531	41K23320A	365916	41E13320A	446790	-	-		
	63A	41K14006A	4800	41K24006A	5090	41E14006A	7734	41E10001A	1851		
B3	100A	41K14010A	6451	41K24010A	6705	41E14010A	9859	41E10002A	2719		
	CD125A	41K14011A	8323	41K24011A	8783	41E14011A	12271				
B4	125A	41G14013A	9987	41G24013A	10102	41E14013A	14644	41E10003A	2906		
	160A	41G14016A	10862	41G24016A	11103	41E14016A	16058				
B5	200A	41G14020A	13199	41G24020A	13526	41E14020A	18542	41E10004A	4283		
	250A	41G14025A	19051	41G24025A	19506	41E14025A	25783				
B6	315A	41G14031A	20333	41G24031A	20391	41E14031A	26979	41E10005A	4587		
	400A	41G14040A	29912	41G24040A	30076	41E14040A	39447				
B7	630A	41G14063A	34930	41G24063A	35040	41E14063A	45706	41E10006A	10198		
	CD800A	41G14079A	48636	41G24079A	49771	-	-				
B8	1000A	41K14100A	88746	41K24100A	88622	41E14100A	120177	41E10007A	32104		
	1250A	41K14120A	118544	41K24120A	118129	41E14120A	166162				
B9	1600A	41K14160A	140244	41K24160A	139622	41E14160A	221719	41E10008A	41322		
	2000A	41K14200A	212112	41K24200A	213584	41E14200A	292301				
B10	2500A	41K14250A	290049	41K24250A	294416	41E14250A	388872	-	-		
	3200A	41K14320A	397320	41K24320A	402738	41E14320A	511678	-	-		

NEW SIRCOVER

CD - Compact Design

1) please refer technical literature for exact technical characteristics

* Phase Barrier & Shaft is not available in B2

Rating 800A is also available in AC-33A category

*Old Sircover from 125A-CD800A are available till stock last



Frame	Direct Handle	LP (₹)	External Handle	LP (₹)	Shaft 200mm	LP (₹)	Shaft 320mm	LP (₹)
B2	42990002A	451	-	-	-	-	-	-
B3	41995012A	901	14212113A	1432	14001020A	416	14001032A	583
B4	41995012A	901	14212113A	1432	14001020A	416	14001032A	583
B5	41995012A	901	14212113A	1432	14001020A	416	14001032A	583
B6*	27997052A	2333	14433113A	3446	14011520A	871	14011532A	1071
B7*	27997052A	2333	14433113A	3446	14011520A	871	14011532A	1071
B8*	27997012A	2697	14538113A	12150	27993015A	2823	27993018A	3121

* double arms handle



Frame	Interphase barrier 3P	LP (₹)	Interphase barrier 4P	LP (₹)	1st or 2nd Aux Contact (1 NO/NC)	LP (₹)	Interlock Kit*	LP (₹)
B2	-	-	-	-	42091030A	530	42590002A	689
B3	29985036A	347	29985039A	504	41090021A	551	42590003A	689
B4	29985026A	413	29985029A	598	41090021A	551	42590003A	689
B5	29985016A	479	29985019A	694	41090021A	551	42590003A	689
B6	-	-	-	-	41090021A	551	-	-
B7	-	-	-	-	41090021A	551	-	-
B8	-	-	-	-	41090021A	551	-	-

* for external operation of Kit 1, interlock kit can be used

* for using Interlock kit in K2, direct handle to be ordered extra

NEW

Rating	Old changeover switch (COS)		Retrofit Solutions	
	Reference	Switch Reference	Kit Reference	LP (₹)
125A	GC01 254POI	41G1 4013A	41RT 4020A	2048
160A	GC01 604POI	41G1 4016A	41RT 4020A	2048
200A	GC02 004POI	41G1 4020A	41RT 4020A	2048
250A	GC02 504POI	41G1 4025A	41RT 4031A	2363
315A	GC03 204POI	41G1 4031A	41RT 4031A	2363
630A	GC06 304POI	41G1 4063A	41RT 4061A	3413

* for 400 A, please consult us.

* above list price is only for retrofit kit, for switch prices please refer page no. 7


* To replace Socomec old changeover (COS), use **RETROFIT KIT** along with the NEW SIRCOVER with direct handle option



Sircover Bypass




Conforms to IS/IEC 60947-3 AC-23A¹, front operated 4 pole 415 V, 50 Hz.

SIRCOVER BYPASS Accessories

SOLUTION		OPEN EXECUTION		
		SIRCOVER BYPASS		
Standard Configuration Includes		 <ul style="list-style-type: none"> • Switch • Interphase barrier • External Handle • Bridging Bars • Shaft 200mm 		
				Rating
	4P	125A	41K29013A	17428
		160A	41K29016A	19231
		200A	41K29019A	21844
		250A	41K29025A	31571
		400A	41K29039A	47936
		500A	41K29050A	55057
		630A	41K29063A	55124
		800A	41K29080A	122226
		1000A	41K29100A	174124
		1250A	41K29120A	197407
	1600A	41K29160A	260519	

1) Please refer technical literature for exact characteristics

Sircover Bypass

Rating								
	External Handle	LP (₹)	Shaft 200mm	LP (₹)	Shaft 320mm	LP (₹)	1st Aux Contact (1NO/NC)	LP (₹)
125A	14212113A	1432	14001020A	416	14001032A	583	41090021A	551
160A	14212113A	1432	14001020A	416	14001032A	583	41090021A	551
200A	14212113A	1432	14001020A	416	14001032A	583	41090021A	551
250A	14333113A	2749	14011520A	871	14011532A	1071	41090021A	551
400A	14333113A	2749	14011520A	871	14011532A	1071	41090021A	551
500A	14333113A	2749	14011520A	871	14011532A	1071	41090021A	551
630A	14333113A	2749	14011520A	871	14011532A	1071	41090021A	551
1250A	41997146A	2749	27993015A	2823	27993018A	3121	41090021A	551
1600A	41997146A	2749	27993015A	2823	27993018A	3121	41090021A	551

When it comes to transfer switching equipment, opt for reliability



from 40 to 6300 A



ATyS: a complete range of transfer switching equipment for every application from 40 to 6300 A

ATyS is remotely operated or fully automatic transfer switching equipment (TSE) assures the continuity of power to a load in a safe and reliable way.

- **Wider range of ATyS** products for different applications. With or without dual power supply, ATS controller, Communication, Software and more.
- **Tested in full compliance** with IEC 60947-6-1 & IEC 60947-3.
- **Unique lateral movement design** with self cleaning contacts ensure high performance and power availability.
- **Wide band control voltage** 166 - 332 V for motor.
- **Self diagnostic watchdog relay** for the motor and controller.
- **3-positions (I-0-II) pad lockable** with 100% manual on-load transfer feasibility with operating handle.



Safe



Plug & play



Robust



Easy maintenance

To find out more:



24/7 ExpertCare Center
1800 203 0456



www.socomec.co.in





socomec
Innovative Power Solutions







Remote & Automatic operated transfer switches

ATyS

Conforms to IEC 60947-6-1, IS/IEC 60947-3, 4 pole

SOLUTION		Remotely Operated							
		ATyS S		ATyS Sd		ATyS S 12Vdc		ATyS S 24Vdc	
Standard Configuration Includes									
		<ul style="list-style-type: none"> • Switch • Handle • Bridging Bars 		<ul style="list-style-type: none"> • Switch • Handle • Bridging Bars • Dual Power Supply 		<ul style="list-style-type: none"> • Switch • Handle • Bridging Bars 		<ul style="list-style-type: none"> • Switch • Handle • Bridging Bars 	
Rating	Poles	Reference	LP (₹)	Reference	LP (₹)	Reference	LP (₹)	Reference	LP (₹)
40A	4P	95034004SL	20635	95134004SL	22906	95054004SL	20635	95064004SL	20635
63A		95034006SL	21785	95134006SL	23947	95054006SL	21574	95064006SL	21574
80A		95034008SL	23450	95134008SL	26030	95054008SL	23450	95064008SL	23450
100A		95034010SL	26521	95134010SL	29153	95054010SL	26264	95064010SL	26264
125A		95034012SL	28415	95134012SL	31236	95054012SL	28139	95064012SL	28139

SOLUTION		Remote Operated		Automatic Transfer Switch Equipment (ATSE)					
		ATyS d M		ATyS t M		ATyS g M		ATyS p M	
Image = 4P B4 Frame									
Standard Configuration Includes		<ul style="list-style-type: none"> • Switch • Handle • Aux Contact 		<ul style="list-style-type: none"> • Switch • Handle 		<ul style="list-style-type: none"> • Switch • Handle 		<ul style="list-style-type: none"> • Switch • Handle 	
Rating	Poles	Reference	LP (₹)	Reference	LP (₹)	Reference	LP (₹)	Reference	LP (₹)
40A	4P	93234004G	37145	93444004G	38590	93544004G	57163	93644004G	On Request
63A		93234006G	39544	93444006G	40764	93544006G	59856	93644006G	On Request
80A		93234008G	42098	93444008G	42938	93544008G	62409	93644008G	On Request
100A		93234010G	42234	93444010G	44025	93544010G	62547	93644010G	On Request
125A		93234012G	47625	93444012G	48645	93544012G	67937	93644012G	On Request
160A		93234016G	57281	93444016G	59244	93544016G	77593	93644016G	On Request

* Please consult us, for 2Pole ATyS M

* These products are DIN rail mountable, please refer to catalogue for more information



Remote & Automatic operated transfer switches

ATyS

Conforms to IEC 60947-6-1, IEC 60947-3, 4 pole

SOLUTION		Remotely Operated		Automatically operated							
		ATyS r		ATyS A		ATyS C		ATyS g		ATyS p	
Standard Configuration Includes											
		<ul style="list-style-type: none"> Switch Handle Bridging Bars up to 1600A 		<ul style="list-style-type: none"> Switch Handle Bridging Bars up to 1600A A15 controller Wire-harness with voltage tags 		<ul style="list-style-type: none"> Switch Handle Bridging Bars up to 1600A C25 controller Wire-harness with voltage tags 		<ul style="list-style-type: none"> Switch Handle Bridging Bars up to 1600A Voltage Sensing Kit 		<ul style="list-style-type: none"> Switch Handle Bridging Bars up to 1600A Voltage Sensing Kit 	
Rating	Poles	Reference	LP (₹)	Reference	LP (₹)	Reference	LP (₹)	Reference	LP (₹)	Reference	LP (₹)
125A	4P	95234012SL	52752	95154012SL	73180	95254012SL	79700	95534012SLVR	On Request	95734012SLVR	On Request
160A		95234016SL	54104	95154016SL	74535	95254016SL	81055	95534016SLVR	On Request	95734016SLVR	On Request
200A		95234020SL	55390	95154020SL	75820	95254020SL	82340	95534020SLVR	On Request	95734020SLVR	On Request
250A		95234025SL	69104	95154025SL	89535	95254025SL	96055	95534025SLVR	On Request	95734025SLVR	On Request
315A		95234031SL	70175	95154031SL	90605	95254031SL	97125	95534031SLVR	On Request	95734031SLVR	On Request
400A		95234040SL	87316	95154040SL	107745	95254040SL	114265	95534040SLVR	On Request	95734040SLVR	On Request
500A		95234050SL	93744	95154050SL	114175	95254050SL	120695	95534050SLVR	On Request	95734050SLVR	On Request
630A		95234063SL	110887	95154063SL	131315	95254063SL	137835	95534063SLVR	On Request	95734063SLVR	On Request
800A		95234080SL	151265	95154080SL	171895	95254080SL	178415	95534080SLVR	On Request	95734080SLVR	On Request
1000A		95234100SL	182667	95154100SL	203300	95254100SL	209815	95534100SLVR	On Request	95734100SLVR	On Request
1250A		95234120SL	226593	95154120SL	247220	95254120SL	253740	95534120SLVR	On Request	95734120SLVR	On Request
1600A		95234160SL	281232	95154160SL	301860	95254160SL	308380	95534160SLVR	On Request	95734160SLVR	On Request
2000A		95234200G	410663	95154200G	431290	95254200G	437815	95534200VR	On Request	95734200VR	On Request
2500A		95234250G	453899	95154250G	474530	95254250G	481050	95534250VR	On Request	95734250VR	On Request
3200A		95234320G	583549	95154320G	604175	95254320G	610700	95534320VR	On Request	95734320VR	On Request

Please contact us for 3Pole ATyS range

* For rating 4000A to 6300A - Prices are available on request

ATyS Accessories



References	Description	LP (₹)
95992010G	HMI ATyS D10 compatible with ATyS d, t, g, p	6720
95992020G	HMI ATyS D20 compatible with ATyS p, ATyS p M	7560
16000015	ATS CONTROLLER ATyS A15 for RTSE products	17930
16000025	ATS CONTROLLER ATyS C25 for RTSE products	24450
13094006G	Bridging bars 40A - 125A for ATyS M	3844
13094016G	Bridging bars 160A for ATyS M	7394
13091001G	1st Auxiliary contact 40 - 160 A for ATyS M with 1 C/O contact for position I,0&II	3792
13994006G	Voltage sensing tap for ATyS M	3163
22944016G	Terminal Shrouds for ATyS M	746
48250204G	Ethernet Module with RS 485 for ATyS p/DirisA40/41 (MODBUS gateway & with Embedded Webserver)	33327
48250203G	Ethernet Module for ATyS p/Diris A40/41 (MODBUS TCP or RTU over TCP protocol & with Embedded Webserver)	17097
48250092G	RS 485 Modbus Communication for ATyS p/Diris A40/41	4344
15992001G	2 Inputs/ Output modules for ATyS p	7839
15994001G	Dual Power Supply for ATyS S & ATyS r	12520

* For high-end controller please contact us



SO expert



www.socomec.co.in

Optimise your energy performance with Socomec

Metering

Measurement and monitoring multi-circuit system
DIRIS Digiware



Single-circuit energy meters
COUNTIS E



Measure

Measurement and monitoring multi-circuit system
DIRIS Digiware




Single-circuit measurement units
DIRIS A



Single & Three phase energy meters
COUNTIS M



Electrical network analyser
DIRIS Q800



Centralise/ Monitor/ Analyse

Communication gateway
DIRIS G



Energy management software
WEBVIEW



24/7 ExpertCare Center
1800 203 0456



www.socomec.co.in

socomec
Innovative Power Solutions

SOCOMECH INDIA PRIVATE LIMITED · 756, Pace City - II Sector 37 Gurgaon -122002, Haryana, India
Tel. +91 44 3921 5466 · Mobile: +91 9711229993 · Email: info.in@socomec.com · CIN: U00000HR1999PTC038504

Measurement and energy management



COUNTIS (LCD Display)



References	Description	LP (₹)
48503019G	COUNTIS E00 1PH,Direct 32A,Active Energy Meter,1 Module width(18 mm) with vertical LCD display	6165
48503039G	COUNTIS E03 1PH,Direct 40A,Active Energy Meter,1 Module width(18 mm) with vertical LCD display with MODBUS	8093
48503000G	COUNTIS E10 1PH Direct 63A,Active Energy Meter with pulse output	8860
48503001G	COUNTIS E11 1PH Direct 63A,Dual tariff, Active Energy Meter with pulse output	9448
48503043G	COUNTIS E13 1PH Direct 80A,Dual tariff, Active Energy Meter with MODBUS	19121
48503047G	COUNTIS E17 1PH Direct 80A,Dual tariff, Active Energy Meter with Ethernet	31927
48503003G	COUNTIS E20 3PH Direct 63A,Active Energy Meter with pulse output	13558
48503004G	COUNTIS E21 3PH Direct 63A Dual tariff, Active Energy Meter with pulse output	14602
48503050G	COUNTIS E23 3PH Direct 80A,Dual tariff, Active Energy Meter with MODBUS	25505
48503054G	COUNTIS E27 3PH Direct 80A,Dual tariff, Active Energy Meter with Ethernet	43018
48503005G	COUNTIS E30 3PH Direct 100A,Active Energy Meter with pulse output	17401
48503006G	COUNTIS E31 3PH Direct 100A Dual tariff, Active Energy Meter with pulse output	17715
48503012G	COUNTIS E33 3PH Direct 100A,Dual tariff, Active Energy Meter with MODBUS	27519
48503008G	COUNTIS E40 3PH Active Energy Meter via CT/5A upto 6000 A	12089
48503009G	COUNTIS E41 3PH Dual Tariff Active Energy Meter via CT/5A upto 6000 A	13371
48503017G	COUNTIS E43 Dual Tariff Active Energy Meter via CT/5A upto 6000 A & with RS485	24020
48503016G	COUNTIS E63 3x1PH Direct 100A ,Active Energy Meter & with RS485	27686
48530000G	COUNTIS ECi2 Multi-Utility Pulse concentrator With upto 7 Insulated Logical inputs	25662
48530001G	COUNTIS ECi3 Multi-Utility Pulse concentrator With upto 7 Insulated Logical inputs+ 2 Analog inputs	29508



COUNTIS 'M' Series

References	Description	LP (₹)
48C03018G	Countis M03 : 45A direct - with Modbus communication via RS485; I,V,P,Q,S ,PF & 2Pulse Output	5899
48C03019G	Countis M13 : 100 A direct - with MODBUS communication via RS485; I,V,P,Q,S ,PF & 2Pulse Output	6064
48C03020G	Countis M33 : 100 A direct - with MODBUS communication via RS485; I,V,P,Q,S ,PF,load curves and THD & 2Pulse Output	9300
48C03021G	Countis M43 : CT 5A input with RS485 MOSBUS communication; I,V,P,Q,S ,PF,load cuves and THD & 2Pulse Output	10309



Measurement and energy management

DIRIS (with LCD multiline display with accuracy class upto 0.5s)



References	Description	LP (₹)
48250010G	DIRIS A10 W/O RS485, class 0.5s, V, I, F, P, Q, S, PF, kWh, kVARh, THDi & V, Dual source	13676
48250011G	DIRIS A10 With RS485, class 0.5s, V, I, F, P, Q, S, PF, kWh, kVARh, THDi & V, Dual source	16556
48250402G	DIRIS A20, class 0.5s, V, I, F, P, Q, S, PF, kWh, kVARh, max kW, kVA, kVAR, THDi & V up to 50th row	14442
48250080G	1 OUT A20 module	3417
48250082G	RS485 A20 module	3541
48250403G	DIRIS A30, class 0.5s, V, I, F, P, Q, S, PF, kWh, kVARh, kVAh, max & Avg(I, V, PF, kW, kVA, kVAR), THDi, V & I up to 63rd row, 3ph current bar graph	17618
48250500G	Diris A40 RS485, 3I 2O, CI 0.2, V, I, F, P, Q, S, PF, kWh, kVARh, kVAh, max & Avg(I, V, PF, kW, kVA, kVAR), THDi, V & I up to 63rd row, PQM Device for Voltage Sag, Swell & Current rise recordings	37838
48250501G	Diris A40 Ethernet, 3I 2O, CI 0.2, V, I, F, P, Q, S, PF, kWh, kVARh, kVAh, max & Avg(I, V, PF, kW, kVA, kVAR), THDi, V & I up to 63rd row, PQM Device for Voltage Sag, Swell & Current rise recordings, webserver function inbuilt	45287
48250502G	Diris A40 Profibus, 3I 2O, CI 0.2, V, I, F, P, Q, S, PF, kWh, kVARh, kVAh, max & Avg(I, V, PF, kW, kVA, kVAR), THDi, V & I up to 63rd row, PQM Device for Voltage Sag, Swell & Current rise recordings	46636
48250202G	DIRIS A41, features same as DIRIS A30 + actual neutral current measurement through 4th CT	33151
48250207G	DIRIS A 60, features same as DIRIS A30 + PQM Device for Voltage Sag, Swell & Current rise recordings	63926
48250090G	2 Pulse A30/A41 module	3392
48250092G	RS 485 Modbus Communication for ATyS p/Diris A30/A41	4323
48250093G	2 0/4-20mA Analog Output module A30/A41	8702
48250094G	2IN/2OUT A30/A41 module for alarm/trip purposes for Max V, I, F, P, Q, S, Temp, THD, V & I parameters	6289
48250097G	MEMORY A30/A41 module with RTC & with storage for P+, P-, Q+, Q-, last Max/Min values for V, I, F, P, Q, THD, V & I	13417
48250203G	Ethernet Module for ATyS p/Diris A30/A41 (MODBUS TCP or RTU over TCP protocol & with Embedded Webserver)	16622
48250204G	Ethernet Module with RS 485 for ATyS p/Diris A30/A41 (MODBUS gateway & with Embedded Webserver)	33169
48250205G	PROFIBUS-DP A30 module	16305
48250206G	Temperature module - Temp indication (Internal+3 External sensors PT 100)	15280

* Upto max 4 modules possible & in that upto 3 nos, 2IN/2OUT & for balance modules max 1 no. can be fitted.

** Upto max 3 modules possible & in that upto 3 nos, 2IN/2OUT & for balance modules max 1 no. can be fitted.

DIRIS G

RS 485 to Ethernet communication gateways

References	Description	LP (₹)
48290300G	Diris G 30 RS485/Ethernet - Webview Power Monitoring	On request
48290302G	Diris G 50 RS485/Ethernet - Webview Power & Energy Monitoring	On request

DIRIS Q800



References	Description	LP (₹)
48260100G	Diris Q800 Electrical network analyser with 192 x 144 mm color touchscreen for power quality/flicker/transient measurements/current waveform/Fresnel diagram	On request

DIRIS Digiware

Measurement and monitoring system for electrical installations



MONITORING DEVICES & MODULES

References	Description	LP (₹)
48290010G	DIRIS B-10 RS485-MODBUS-230VAC	On request
48290000G	DIRIS B-30 RS485-MODBUS-230VAC	
48290030G	DIRIS O-iod DIGITAL MODULE	
48290031G	DIRIS O-ioa 0/4-20mA MODULE	
48290032G	DIRIS O-it TEMPERATURE MODULE	
48290033G	DIRIS O-m MODBUS RS485 MODULE	
48290034G	DIRIS O-p PROFIBUS DP MODULE	
48290035G	DIRIS O-b/ip BACNET MODULE	
48290036G	DIRIS O_b/mstp BACNET MODULE	



POWER SUPPLY

References	Description	LP (₹)
48290120G	P15 AUX SUPPLY 100-240VAC->24 VDC 15W	On request
47290603G	P30 AUX SUPPLY 100-240VAC->24 VDC 30W	



DIRIS G GATEWAY

References	Description	LP (₹)
48290300G	DIRIS G-30 RS/ETH MONITORING	On request
48290302G	DIRIS G-50 RS/ETH MONIT+REPORT	



DISPLAY

References	Description	LP (₹)
48290200G	DIRIS D-30 Single-point display	On request
48290199G	DIRIS D-40 Multi-point display - RS485 output	
48290204G	DIRIS D-50 Multi-point display - Ethernet output - Dual channel input(Digibus & modbus)	
48290203G	DIRIS D-70 Multi-point display - Webview Webserver - Ethernet output	



BLIND INTERFACE & REPEATER

References	Description	LP (₹)
48290101G	C-31 SYSTEM INTERFACE	On request
48290103G	C-32 REPEATER	



VOLTAGE SENSING MODULE

References	Description	LP (₹)
48290105G	U-10 VOLTAGES INPUTS METERING	On request
48290106G	U-20 VOLTAGES INPUTS MONITORING	
48290102G	U-30 VOLTAGES INPUTS ANALYSIS	



CLOSED TYPE CURRENT SENSOR

References	Description	LP (₹)
48290500G	TE-18 20A SOLID CORE	On request
48290501G	TE-18 63A SOLID CORE	
48290502G	TE-25 160A SOLID CORE	
48290503G	TE-35 250A SOLID CORE	
48290504G	TE-45 630A SOLID CORE	
48290505G	TE-55 1000A SOLID CORE	
48290506G	TE-90 2000A SOLID CORE	



OPEN TYPE CURRENT SENSOR

References	Description	LP (₹)
48290551G	TR-10 75A/100MV SPLIT CORE	On request
48290552G	TR-16 100A/100MV SPLIT CORE	
48290553G	TR-24 200A/100MV SPLIT CORE	
48290554G	TR-36 600A/100MV SPLIT CORE	





Measurement and energy management

CURRENT SENSING MODULE



References	Description	LP (₹)
48290110G	I-30 3xl METERING	On request
48290111G	I-31 3xl METERING + TREND	
48290112G	I-60 6xl METERING	
48290113G	I-61 6xl METERING + TREND	
48290128G	I-33 3xl MONITORING	
48290130G	I-35 3xl ANALYSIS	
48290129G	I-43 4xl MONITORING 2I/2O	
48290131G	I-45 4xl ANALYSIS 2I/2O	

FLEXIBLE CURRENT SENSOR



References	Description	LP (₹)
48290570G	TF-55 600A ROGOWSKI	On request
48290571G	TF-120 2000A ROGOWSKI	
48290572G	TF-300 6000A ROGOWSKI	

RJ45 CABLES



References	Description	LP (₹)
48290181G	RJ45-0.32 feet / 0.10m CABLE	On request
48290188G	RJ45-0.64 feet / 0.20m CABLE	
48290182G	RJ45-1.64 feet / 0.50m CABLE	
48290183G	RJ45-3.28 feet / 1m CABLE	
48290184G	RJ45-6.56 feet / 2m CABLE	
48290186G	RJ45-16.4 feet / 5m length CABLE	
48290187G	RJ45-32.8 feet / 10m length CABLE	
48290185G	RJ45 cables for BUS Digiware 164 feet / 50 m + 50 connectors	

RJ12 CABLES



References	Description	LP (₹)
48290580G	RJ12 3x0.1m CABLE	On request
48290581G	RJ12 3x0.2m CABLE	
48290582G	RJ12 3x0.3m CABLE	
48290583G	RJ12 3x1m CABLE	
48290584G	RJ12 3x2m CABLE	
48290585G	RJ12 4x0.1m CABLE	
48290586G	RJ12 4x0.2m CABLE	
48290587G	RJ12 4x0.3m CABLE	
48290588G	RJ12 4x1m CABLE	
48290589G	RJ12 4x2m CABLE	
48290590G	RJ12 6x0.1m CABLE	
48290591G	RJ12 6x0.2m CABLE	
48290592G	RJ12 6x0.3m CABLE	
48290593G	RJ12 6x1m CABLE	
48290594G	RJ12 6x2m CABLE	
48290595G	RJ12 3x0.5m CABLE	
48290596G	RJ12 4x0.5m CABLE	
48290597G	RJ12 6x0.5m CABLE	
48290602G	RJ12 1 cable of 16.6ft/5m	
48290603G	RJ12 1 cable of 32.8ft/10m	
48290601G	RJ12 1 Cable of 164ft/50m and 50 connectors	

ACCESSORIES

References	Description	LP (₹)
48290049G	SEALING KIT DIRIS B30	On request
48290050G	USB CONFIGURATION CABLE	
48290180G	END LINE RESISTANCE RJ45	
48290598G	SPLICE PLATE x30	
48290599G	CT/5A to 100 MV ADAPTOR	
48290600G	SEALABLE COVER x20	
48290280G	RJ9 1x1,5m	
48290281G	RJ9 1x3m	




Discontinued Products

Available till stock lasts


Load Break Switches (LBS)

Conforms to IS/IEC 60947-3 AC-23A1,
Front operated 4 pole 415 V, 50 Hz

SOLUTION		OPEN EXECUTION	
Standard Configuration Includes		 <ul style="list-style-type: none"> • Switch • Inter Phase Barriers ≥800A • Direct Handle • Door Interlock • 1st Aux Contact ≥250A 	
250A	4P	GL02504POI	11604
320A		GL03204POI	12495
400A		GL04004POI	17365
630A		GL06304POI	20932
1000A		GL10004POI	47670
2000A		GL20004POI	109228


Changeover switches (COS)

Conforms to IS/IEC 60947-3, AC-23A1,
Front operated 4 pole 415 V, 50 Hz

SOLUTION		OPEN EXECUTION	
Standard Configuration Includes		Switch	
		 <ul style="list-style-type: none"> • Switch • Handle • Bridging Bars • Door Interlock Assembly • Phase Barrier ≥800A • 1st Aux Contact ≥ 250A 	
Rating	Poles		
630A	4P	GC06304POI	44252
1000A		GC10004POI	107604
1250A		GC12504POI	143430
1600A		GC16004POI	169529

Bypass changeover switches (BPCOS)

Conforms to IS/IEC 60947-3 AC-23A1, Front operated 4 pole 415 V, 50 Hz

SOLUTION		OPEN EXECUTION	
Standard Configuration Includes		Switch	
		 <ul style="list-style-type: none"> • Switch • Inter Phase Barriers ≥800A • Direct Handle • Bridging Bars • 1st Aux Contact ≥250A 	
Rating	Poles		
250A	4P	GBP02504POI	30357
1250A		GBP12504POI	189814
1600A		GBP16004POI	250499

MULTIS "m" Series(LED/LCD display)



References	Description	LP (₹)
192J9013G	Multis Vm15 1ph, 1L, CL1 Prg	1173
192J9014G	Multis Vm15 1ph, 1L, CL1	1020
192J9103G	Multis Lm42 LCD AC Kwh CL1	3621
192J9111G	Multis Lm45 3Ph/3L MFM CL1	7650
192J9112G	Multis Lm46 3Ph/3L MFM CL1 Com	8486
192J9113G	Multis Lm42 LCD AC-Kwh CL1 Com	4307
192J9200G	Multis L55 MFM THD CL1 Com	14053

SOCOMEK India

General terms and conditions

1. PRICES

All Prices are mentioned in Indian Rupees. Prices are subjected to change without any prior notice will be applicable as prevailing at the time of Dispatch. This Price list is effective from June 30th 2021 and supersedes any previous price list.

2. TAXES & DUTIES

The prices are exclusive of all taxes

We will charge applicable Goods and Services Tax ('GST') on our supplies

In the event of variations in rate of tax, rules and/or method of assessment under the GST, the prices will be adjusted accordingly.

It will be the responsibility of customer to communicate its correct GSTIN to the Company. Company will not be responsible in case incorrect GSTIN is communicated to us and tax is deposited by us on GSTIN available in Company's record

3. WARRANTY

The Company warrants the goods against all proven defects or hidden defects in design and manufacturing. The period of warranty is 12 months from date of invoicing or 18 months from date of manufacturing. The warranty shall be strictly limited to Socomec products and does not extend to the equipment within which these products may be integrated or not to the performance of such equipment. The Company's warranty shall be limited, in its discretion, to the repair or replacement at its expense in its factory of all part of the goods recognized as defective. Defective items replaced free of charge shall be made available to the company and shall become its property. The warranty shall not be applicable.

- 3.1 In the event that the defect if due to the material supplied by the buyer, or due to design imposed by it.
- 3.2 In the event of damage or accident due to the transport or arising from negligence, defective installation, supervision or maintenance by the buyer or a third party.
- 3.3 In the event of use, installation or storage of the goods in abnormal conditions which are not in compliance.
- 3.4 In the event of any changes, adjustments or repairs carried out by buyer without express agreement of the company.

The warranty does not cover the replacement or repair of the items which are due to the fault of the buyer or third party.

Our Service Partners



Socomec: our innovations supporting your energy performance

1 independent manufacturer

3,600 employees
worldwide

10 % of sales revenue
dedicated to R&D

400 experts
dedicated to service provision

Your power management expert



POWER
SWITCHING



POWER
MONITORING



POWER
CONVERSION



ENERGY
STORAGE



EXPERT
SERVICES

The specialist for critical applications

- Control, command of LV facilities
- Safety of persons and assets
- Measurement of electrical parameters
- Energy management
- Energy quality
- Energy availability
- Energy storage
- Prevention and repairs
- Measurement and analysis
- Optimisation
- Consultancy, commissioning and training

A worldwide presence

12 production sites

- France (x3)
- Italy (x2)
- Tunisia
- India
- China (x2)
- USA (x3)

28 subsidiaries and commercial locations

- Algeria • Australia • Belgium • China • Canada
- Dubai (United Arab Emirates) • France • Germany
- India • Indonesia • Italy • Ivory Coast • Netherlands
- Poland • Portugal • Romania • Serbia • Singapore
- Slovenia • South Africa • Spain • Switzerland
- Thailand • Tunisia • Turkey • UK • USA

80 countries

where our brand is distributed

Manufacturing facility

Socomec India Private Limited.
756 Pace City II
Sector 37
Gurgaon - 122 001
Haryana
Tel: +91 124 4562700, 4597803
Fax: +91 124 4562733
CIN: U00000HR1999PTC038504

Regional & resident offices

Ahmedabad : +91 9987052602, +91 8939008184
Bengaluru : +91 9972578171, +91 9886323448
Chennai : +91 9940147003, +91 9176611256
Cochin : +91 9745012322, +91 8939550688
Coimbatore : +91 9500092236, +91 8939550688
Hyderabad : +91 7338733982, +91 9642528800
Indore : +91 9953595413

Kolkata : +91 9836207671, +91 7550048077
Mumbai : +91 9987947506, +91 8879791802
New Delhi : +91 9958591713, +91 9953595413
Pune : +91 9987052604, +91 8793144968
Trivandrum : +91 9745012322, +91 8939550688
Vadodara : +91 9987052602, +91 8939008184
Vijaywada : +91 9515100473



SOCOMEK INNOVATIVE POWER SOLUTION PVT. LTD.

B1, II Floor
Thiru-Vi-Ka Industrial Estate
Guindy, Chennai - 600 032
Tel: +91 44 3921 5400 / 5423 / 5466
Mob: +91 9711229993, +91 9940633654
info.in@socomec.com

YOUR DISTRIBUTOR / PARTNER

www.socomec.co.in

