Hinged Flood Barriers PS Flood Barriers



Hinged Flood Barriers are designed specifically for the height of water protection you require. The barriers are permanently installed and stored in the open position. During flooding, the Hinged Flood Barrier is swung closed and is latched, providing flood protection. The Hinged Flood Barrier is available in a single swing or paired swing configuration.

The Hinged Flood Barrier comes in two variations. The HSS-550 is a single swing flood barrier and the HPS-555 is a "paired swing" flood barrier. Depending upon the layout of your facility, the offering of a single or paired hinged barrier allows for flexibility when designing the flood protection system.

Standard Features:

- Available in mild steel, stainless steel, or aluminum.
- Compression seal—requires no compressed air for activation.
- Latch system designed for simple, quick deployment.

Application Use:

- Walk doors.
- Sectional doors.
- Retaining walls.
- Driveways.
- Store fronts.
- Interior hallways/room.

Benefits:

- Quick placement when needed.
- Can be done with or without a raised sill.
- Minimum personnel needed to close flood barriers.

Custom sizing and design available.

877.446.1519 flooddoors.com

Safe. Simple. Durable.

Made in USA.

ISO9001:2008

CERTIFIED

25 DOORS

PS DOORS

Attn: PS Flood Barrlers 1150 South 48th Street Grand Forks, ND 58201 Phone: 701.746.4519 Toll Free: 877.446.1519 Email: 4psinfo@psdoors.com

Rev. 091516