



Motorised and automatic changeover switches from 125 to 3200 A





A totally safe transfer, whatever the application

The design of the products in the ATyS family, based on proven load break switch technology, guarantees both the continuity of the power supply and the safety of operators. Its stable positions allow energy consumption to be minimised whilst ensuring maximum immunity to electrical network disturbances, making this a truly robust and reliable solution.



Ensures availability of the electrical power supply under all circumstances

The functions and design of the ATyS product range all work towards one key objective: ensuring the supply of loads downstream, via **rapid transfer** from one source to another. These products have three operating modes, which increase the ability to select the most reliable source **under all circumstances**. The products only require a power supply when changing position, which increases

their reliability and service life.

Simplicity ensures safety

Thanks to their on-load switching capacity, coupled with their Auto and Manual operating modes, the ATyS are simple to use and 100% secure. The selection of the power supply source to the load can be achieved in three different ways:


- using the front operation handle (Manual mode).
- remotely, using the input for position control commands (Auto mode),
- automatically, depending on the availability of sources (Auto mode).
 To ensure technical interventions downstream of the product are as secure as possible, ATyS have a highperformance padlocking function which is an efficient addition to the breaking functions.

To find out more... Visit our website: www.socomec.com/en/changeover



A complete range of changeover switches, from 125 to 3200 A, adapted to all your applications

Five product versions are available, ensuring a solution suited to your application.



Automatic version (ATS) or motorised version (RTS)?



The ATyS t, ATyS g and ATyS p (ATS) versions differ from the ATyS and ATyS d in that they integrate an automatic controller. This means that the products themselves monitor the availability of sources, start the generators if necessary and automatically switch to the available source.

Conversely, ATyS and ATyS d (RTS), require **an external controller** to provide them with switching commands.

Benefits of the ATyS range



Plug and play solution

Integrated auto-configuration

As standard, all automatic versions have the auto-configuration function which enables automatic setting of the nominal voltages and frequencies for the network. Simply cable the product, which will then measure the values and record them.

Quick installation

All ATyS products are factory assembled and require minimum cabling, thereby simplifying the installation and reducing the amount of time required to be operational.

For ATyS t and ATyS g, configuration adjustment is achieved via potentiometers, requiring only a screwdriver and a few minutes.





Manual emergency control

In the event of an emergency, it can be controlled **quickly**, **easily and safely** using an emergency handle. This handle is very easy to fit and no motorised or automatic transfer can take place when the handle is in place.





Continuous information on product availability

Products in the ATyS range are equipped with a Watchdog relay which **constantly monitors** your product, thereby securing your installation.

This relay informs you of the capacity of your product to switch correctly following an electrical or automatic order.



Robust products

All ATyS product versions are designed and tested in accordance with standard **IEC 60947-6-1**, the benchmark for changeover switches offering optimum design and operating features.

Improved performance

According to IEC 60947-6-1:

- AC 33-B up to 1250 A
- AC 32-B up to 2000 A
- AC 32-B up to 2000 A
 AC 31-B up to 3200 A




Specific genset functions



ATyS g and ATyS p can be utilised for switching between transformer and generator power supply

sources. They have a genset run command and integrate on load and off load test functions. These functions ensure there is a good connection between the source changeover switch and the generator, and that these are both operating correctly.

The ATyS p also allows **scheduled starts** to be programmed for these different tests.



The benefits of ATyS p

Simple configuration software: Easyconfig

The **Easyconfig software** is ideal for reducing the time spent during complex configuration operations.

It allows the following parameters to be configured:

- type of application,
- voltage and frequency thresholds,
- timer values.
- inputs/outputs...




Communication options which make the difference: Modbus, Ethernet and Webserver

Thanks to optional modules, ATyS p communicate using **Modbus** and **Ethernet** protocols.

The Ethernet communication module also integrates the **Webserver** function, allowing the ATyS p to be accessed via a web browser.

The Webserver function enables:

- product status display (product position and source status),
- the display of voltage measurements,
- the display of configured parameters,
- access to the event log.



Additions to the range

ATyS S and ATyS Sd Motorised changeover switches from 40 to 125 A

Specially developed for manufacturers of small generators, ATyS S and Sd enable simultaneous breaking and switching between two power supply sources up to 125 A (< 90 kVA).



ATyS M modular changeover switches from 40 to 160 A

Three versions of ATyS M (remote-controlled and automatic) are available to meet the vast majority of your source switching application requirements.




Selection guide

Which type of 3 or 4		n power	Which	Sune	rvision?
transfer? poles?	sur	oply?	application?	Gapo	Violetti
	ATyS range: products fitted back-to-back 125 to 3200 A				
	ATyS	ATyS d	ATyS t	ATyS g	ATyS p
Type of transfer	711/3	717/5 0	717/31	711/5 8	γγο β
Emergency manual transfer via handle	•	•	•	•	•
Remote controlled transfer using dry contact piloting (RTSE)	•	•	·	·	
Automatic transfer (ATSE)			•	•	•
Number of poles					
3 P	•	•	•	•	•
4 P	•	•	•	•	•
Supply type					
230 VAC single power supply	•				
230 VAC dual power supply		•	•	•	•
Connection of remote control interface					
Remote display D10		•	•	•	•
Remote control interface D20					•
Automatic controller configuration	I				
Configuration by potentiometers and dip switches			•	•	
Configuration by screen and keyboard					•
Auto-configuration of the voltage and frequency			•	•	•
Application					
Generator - Generator applications	• (1)	• (1)			
Network - Generator application	• (1)	• (1)		•	•
Network - Network application	• (1)	• (1)	•		•
Automatic controller functionalities					
Contact for product availability	•	•	•	•	•
Control of voltages and frequency			•	•	•
Control of phase rotation			•	•	•
Phase unbalance control					•
LED display of source availability		•	•	•	•
LED display of positions			•	•	•
On-screen display of meters and voltage/frequency measurements					•
On load and off load test				•	•
Load shedding					•
Display and measurement of power and energies (with CT option)					<u> </u>
Supervision (with optional module)					
Scheduling of generator start-up					•
RS485 communication					•
Ethernet communication					•
Webserver via Ethernet module					•
Data log					•

⁽¹⁾ using an external controller.

References for the ATyS range



SOCOMEC, your best asset

SOCOMEC is an industrial group specialising in the availability, control and safety of low voltage electrical energy which meets the requirements of the industry and the service sector.

Disconnection, breaking, control... Since 1922 Socomec has gained a wealth of experience in these fields. The back-to-back manual changeover switch, designed and manufactured by Socomec and now available in a compact motorised version, has become the world reference in powerswitching.

Four key applications: the know-how of a specialist

Ensuring the availability of high-quality power for critical applications.





Managing power and protecting individuals and property.

Improving the energy efficiency of buildings and facilities.





Guaranteeing the safety and durability of photovoltaic (PV) facilities.











Socomec worldwide

IN EUROPE

BELGIUM

UPS / Power Control & Energy Efficiency / Solar

Tel. +32 2 340 02 30 Fax +32 2 346 28 99 info.be@socomec.com

FRANCE

UPS / Power Control & Energy Efficiency / Solar

Tel. +33 1 45 14 63 00 Fax +33 1 48 67 31 12 dcm.ups.fr@socomec.com

GERMANY

Power Control & Energy Efficiency

Tel. +49 7243 65292 0 Fax +49 7243 65292 13 info.scp.de@socomec.com

UPS

Tel. +49 621 71 68 40 Fax +49 621 71 68 444 info.ups.de@socomec.com

ITALY

Power Control & Energy Efficiency

Tel.+39 02 98 49 821 Fax +39 02 98 24 33 10 info.scp.it@socomec.com

Solar

Tel. +39 0444 598611 Fax +39 0444 598627 info.solar.it@socomec.com UPS

Tel.+39 02 98 242 942

Fax +39 02 98 240 723 info.ups.it@socomec.com

NETHERLANDS

UPS / Power Control & Energy Efficiency / Solar

Tel. +31 30 760 0900 Fax +31 30 637 2166 info.nl@socomec.com

POLAND

Power Control & Energy Efficiency

Tel. +48 91 442 64 11 Fax +48 91 442 64 19 info.scp.pl@socomec.com

UPS

Tel. +48 22 825 73 60 Fax. +48 22 825 73 60 info.ups.pl@socomec.com

PORTUGAL

UPS / Solar

Tel.+351 261 812 599 Fax +351 261 812 570 info.ups.pt@socomec.com

ROMANIA

UPS / Power Control & Energy Efficiency /

Solar Tel. +40 21 319 36 88

RUSSIA

Fax +40 21 319 36 89 info.ro@socomec.com

UPS / Power Control & Energy Efficiency / Solar

Tel. +7 495 775 19 85 Fax +7 495 775 19 85 info.ru@socomec.com

SLOVENIA

UPS / Power Control & Energy Efficiency / Solar

Tel. +386 1 5807 860 Fax +386 1 561 11 73 info.si@socomec.com

SPAIN

UPS / Power Control & Energy Efficiency / Solar

Tel. +34 93 540 75 75 Fax +34 93 540 75 76 info.es@socomec.com

UNITED KINGDOM

Power Control & Energy Efficiency

Tel. +44 1462 440 033 Fax +44 1462 431 143 info.scp.uk@socomec.com

UPS

Tel.+44 1285 863 300 Fax+44 1285 862 304 info.ups.uk@socomec.com

TURKEY

UPS / Power Control & Energy Efficiency / Solar

Tel. +90 216 540 71 20-21-22 Fax +90 216 540 71 27 info.tr@socomec.com

IN ASIA PACIFIC

AUSTRALIA UPS

Tel. +61 2 9325 3900 Fax +61 2 9888 9544 info.ups.au@socomec.com

CHINA

UPS / Power Control & Energy Efficiency

Tel. +86 21 52 98 95 55 Fax +86 21 62 28 34 68 info.cn@socomec.com

INDIA

Power Control & Energy Efficiency

Tel. +91 124 4027210 Fax +91 124 4562738 info.scp.in@socomec.com

UPS / Solar

Tel. +91 44 39215400 Fax +91 44 39215450 & 51 info.ups.in@socomec.com info.solar.in@socomec.com

SINGAPORE

UPS / Power Control & Energy Efficiency

Tel.+65 6506 7600 Fax +65 64 58 7377 info.sg@socomec.com

THAILAND

UPS

Tel. +66 2 941 1644 7 Fax +66 2 941 1650 info.ups.th@socomec.com

VIETNAN

UPS

Tel. +84 8 3559 1220 Fax +84 8 3559 1221 info.ups.vn@socomec.com

IN MIDDLE EAST

UNITED ARAB EMIRATES

UPS / Power Control & Energy Efficiency / Solar

Tel.+971 4 29 98 441 Fax +971 4 29 98 449 info.ae@socomec.com

IN AMERICA

USA, CANADA & MEXICO

Power Control & Energy Efficiency

Tel. +1 617 245 0447 Fax +1 617 245 0437 info.us@socomec.com

OTHER COUNTRIES

NORTH AFRICA

Algeria / Morocco / Tunisia info.naf@socomec.com

AFRICA

Other countries

info.africa@socomec.com

SOUTH EUROPE

Cyprus / Greece / Israel / Malta info.se@socomec.com

SOUTH AMERICA

Tel. +34 93 540 75 75 info.es@socomec.com

MORE DETAILS

www.socomec.com/worldwide

HEAD OFFICE

SOCOMEC GROUP

S.A. SOCOMEC capital 10 816 800€ R.C.S. Strasbourg B 548 500 149 B.P. 60010 - 1, rue de Westhouse F-67235 Benfeld Cedex - FRANCE Tel. +33 3 88 57 41 41 Fax +33 3 88 74 08 00 info.scp.lsd@socomec.com

YOUR DISTRIBUTOR





www.socomec.com







